



How to - European Sidecar Rear Bumper Accessory Installation

How to install the European sidecar rear bumper accessory for all Ural Motorcycles.

Written By: David



**TOOLS:**

- [5mm Hex Key](#) (1)
- [13mm Wrench](#) (2)

**PARTS:**

- [Crash Bar for Sidecar Rear \(Heavy Version\) Black](#) (1)

P/N: 58216.105

Step 1 — How to - European Sidecar Rear Bumper Accessory Installation



- Open trunk and remove contents to gain access to the sidecar trunk hinge mounting hardware.

Step 2



- Use a 13mm tool inside and 5mm hex key outside to remove the four (4) lower sidecar trunk hinge bolts, nuts and washers.

Step 3



- ☑ An anti-seize compound is recommended for all stainless steel hardware to aid in the prevention of galling.
- Use the supplied stainless steel hardware, align the mounting holes of the bumper to those on the sidecar trunk hinges.
- Install ALL the provided stainless steel hardware finger tight.

Step 4



- Center the rear bumper so it is evenly spaced in relation to the sidecar body.
- Use two 13mm tool to tighten the four (4) supplied stainless steel mounting hex bolts, nuts and washers.

Step 5



- Replace contents of trunk and close trunk lid securely.
- Enjoy your new sidecar rear bumper accessory!