

How to - Handlebar Clamp Accessory Ball Mount Installation

A how to guide outlining the installation of the Ural Handlebar Clamp Accessory Ball Mount on 2014 and newer Ural Motorcycles.

Written By: David



INTRODUCTION

This guide outlines the installation of the Ural Handlebar Clamp Accessory Ball Mount P/N: 52001 on 2014 and newer Ural Motorcycles.



TOOLS:

- 6mm Hex Key (1)
- Torque Wrench (1)



PARTS:

 52001 Ural Handlebar Clamp Accessory Ball Mount (1)

Step 1 — How to - Handlebar Clamp Accessory Ball Mount Installation





- Cover the fuel tank to prevent damage while working.
 - The handlebar can rotate down and damage the fuel take when the handlebar clamps are loosened.







- Use a 6mm hex key, loosen and remove all four (4) 8mm bolts from the left and right handlebar clamps.
 - in most cases the 8mm bolts can be reused. Replacement hardware is **NOT** provided with the new top clamp.
 - ⚠ If the 8mm bolts show any sign of rust, scale or corrosion replace the bolts. Only reuse bolts in good sound condition with clean threads.
- Remove the left and right handlebar clamps.





- Place the new one piece handlebar clamp into position.
- Tighten the four (4) 8mm bolts evenly by hand until the handlebar will stay in place without rotating but will allow adjustment.





- Adjust the bars into position best suited to the driver.
- Lock the position in place with the use of a 6mm hex key.





- (not corroded) zinc plated steel hardware to aluminum.
- Torque the four (4) 8mm bolts to 15 Nm (11 ft/lb).
 - (i) If the recommended torque specification allows the handlebars to move or rotate, increase the torque incrementally by 1 Nm (.74 ft/lb) until the handlebars are seated firmly and do not move or rotate.
- ENJOY your new handlebar clamp accessory ball mount! The centrally located, strong and stable design will accommodate most one inch (1") ball mount accessories.